

TECHNICAL SHEET

Thin stems in precious metallic finishes create evocative harmonies of light.

Available in three sizes, Storm is a lamp that can live alone but is designed to be used in groups, in public spaces as well as at home.

Certification



	1905-30
Mounting	Wall sconces
Enviroment	Indoor - Dry location
Materials	Metal
Voltage	120-277V - 50/60Hz
Source	LED 20W - CRI=90
Color Temperature	3000K / 2700K
Lumen	1500lm
Lighting control	Dimmable 0-10V/ Dimmable phase cut (120V only)



1905-30



Finishes

Structure



Matt black



Matt white



Matt titanium

Codes Interpretation

1905 - 30 - 1100 - DXNU

1905

Year Collection

30

Typology Model

1100

Finish1 Finish2

DXNU

Lighting control Cable Source Wiring

CODES	SIZE	STRUCTURE	SHADE	DETAILS
1905-30-1100-DXNU	wall sconces	matt black		dimnable 0-10V / dimmable phase cut (120V only)
1905-30-1100-DXWU	wall sconces	matt black		dimnable 0-10V / dimmable phase cut (120V only)
1905-30-0100-DXNU	wall sconces	matt white		dimnable 0-10V / dimmable phase cut (120V only)
1905-30-0100-DXWU	wall sconces	matt white		dimnable 0-10V / dimmable phase cut (120V only)
1905-30-1800-DXNU	wall sconces	matt titanium		dimnable 0-10V / dimmable phase cut (120V only)
1905-30-1800-DXWU	wall sconces	matt titanium		dimnable 0-10V / dimmable phase cut (120V only)

Legenda

Lighting Control	D = Dimmable	N = Not dimmable	
Cable	X = not suspension lamp	2 = 2m	4 = 4m
Source	B = Bulb	W = Integrated LED 2700K	N = Integrated LED 3000K
Wiring	E = Universal	U = USA with certification	V = USA without certification